



# Rigid Steel Conduit

American Standard Rigid Steel Conduit, Zinc Coated

Trade Size (in.)	Diameter		Nominal Wall Thickness (mm.)	Length without Coupling (mm.)	Min. Acceptable Weight Minimum Weight of 10 Unit Lengths with Coupling, (kgs.)
	Nominal Inside Dia. (mm.)	Outside Diameter (mm.)			
1/2"	16.1	21.1	2.64	3.03	35.83
3/4"	21.2	26.7	2.72	3.03	47.63
1"	27.0	33.4	3.20	3.02	69.40
1 1/4"	35.4	42.2	3.38	3.02	91.17
1 1/2"	41.2	48.3	3.51	3.02	112.95
2"	52.9	60.3	3.71	3.02	150.60
2 1/2"	63.2	73.0	4.90	3.01	239.05
3"	78.5	88.9	5.21	3.01	309.63
3 1/2"	90.7	101.6	5.46	3.00	376.94
4"	102.9	114.3	5.72	3.00	441.04
5"	128.9	141.3	6.22	3.00	595.85
6"	154.8	168.3	6.76	3.00	791.67

**TOLERANCE :**

Outside Diameter  
 ± 0.38 mm (For 1/2" - 2")  
 ± 0.64 mm (For 2 1/4" - 4")

Wall Thickness : - 12.5%  
Length : ± 6.4 mm

