

TYPES KS & KS-3

SERVIT™

For Copper,
Copperweld

Compact, high strength, high copper alloy SERVIT™ split-bolt has free-running threads, and easy to grip wrench flats. Highly resistant to season cracking and corrosion, the SERVIT™ provides maximum pressure and assures secure connection on all combinations of run and tap conductors. Type KS-3, similar to Type KS, accommodates 3 maximum size conductors.



CATALOG NUMBER	CONDUCTOR					
	COPPER		COPPERWELD			
	RANGE FOR EQUAL RUN AND TAP	MIN. TAP WITH MAX. RUN	MAXIMUM			
			SOL.	STR.	TYPE A	TYPE D
KS90	12 Str. - 8 Str.	16 Str.	#10	—	—	—
KS15	10 Str. - 8 Str.	14 Str.	#8	—	—	—
KS17	8 Str. - 6 Sol.	14 Str.	#6	3 #12	8A	9-1/2D
KS17-3*	8 Str. - 6 Sol.	14 Str.	#6	3 #12	8A	9-1/2D
KS20	8 Str. - 4 Sol.	14 Str.	#4	3 #10	6A	8D
KS20-3*	8 Str. - 4 Sol.	14 Str.	#4	3 #10	6A	8D
KS22	6 Str. - 2 Sol.	14 Str.	#2	3 #8	4A	6D
KS22-3*	6 Str. - 2 Sol.	14 Str.	#2	3 #8	4A	6D
KS23	6 Str. - 2 Str.	14 Str.	#1	3 #7	3A	5D
KS25	4 Str. - 1/0 Str.	14 Str.	2/0	3 #5	2A	4D
KS26	2 Str. - 2/0 Str.	14 Str.	3/0	7 #7	—	—
KS27	1 Str. - 3/0 Str.	8 Sol.	—	—	—	—
KS29	1 Str. - 250	8 Str.	4/0	7 #5	—	—
KS31	1/0 Str. - 350	1/0 Str.	—	19 #8	—	—
KS34	2/0 Str. - 500	2/0 Str.	—	19 #6	—	—
KS39	4/0 Str. - 750	4/0 Str.	—	19 #5	—	—
KS44	300 - 1000	4/0 Str.	—	—	—	—

* Not UL or CSA listed.

E-4



TYPE SC

SERVIT™ COVER

HUG-A-BUG

Used indoors or outdoors this compact, one-piece plastic SERVIT™ cover, saves time and material, eliminates costly taping of split-bolts. Positive latch snaps easily and quickly over connector, ideal for tight quarters. Self positioning plastic fingers wrap around wires fully insulating joint. UL listed for 600 volt indoor application. Three covers accommodate a range of 6 SERVIT™ sizes through 2/0 Str.



CATALOG NUMBER	CONDUCTOR RANGE				*FOR USE WITH	FOR USE WITH
	RANGE FOR EQUAL RUN AND TAP		MIN. TAP WITH MAX. CABLE RUN			
	MIN.	MAX.	MIN.	MAX.		
SC4	8 Str.	6 Sol.	14 Str.	6 Sol.	KS17	—
SC4	8 Str.	4 Sol.	14 Str.	4 Sol.	KS20	—
SC2	6 Str.	2 Sol.	14 Str.	2 Sol.	KS22	KSA6
SC2	6 Str.	2 Str.	14 Str.	2 Str.	KS23	KSA4
SC2/0	4 Str.	1/0 Str.	14 Str.	1/0 Str.	KS25	KSA2
SC2/0	2 Str.	2/0 Str.	14 Str.	2/0 Str.	KS26	KSA1/0

* UL listing of Type SC Cover applies to use on BURNDY® SERVIT™ Type KS and to equivalent split-bolt connectors indicated strip length is maintained, maximum indicated

conductor sizes are not exceeded, and connector is properly located within recess provided for it.

