

ALARM BELL



PL-E

■ SPECIFICATIONS

Item No.	RATING	GONG SIZE	MOUNTING STYLE
CB-4B	AC 110V • 220V • 380V	4" (100mm)	SURFACE MOUNTING
CB-6B	AC 12V • 24V • 48V • 110V • 220V • 380V DC • 12V • 24V • 48V	6" (150mm)	SURFACE MOUNTING FLUSH MOUNTING (WITH CB-BBX)
CB-8B	AC 12V • 24V • 48V • 110V • 220V • 380V DC • 12V • 24V • 48V	8" (200mm)	SURFACE MOUNTING FLUSH MOUNTING (WITH CB-BBX)
CB-10B	AC 12V • 24V • 48V • 110V • 220V • 380V DC • 12V • 24V • 48V	10" (250mm)	SURFACE MOUNTING FLUSH MOUNTING (WITH CB-BBX)

■ PILOT LIGHT

Item No.	RATING
PL-E	AC: 110V, 220V DC: 12V, 24V

● BELL

- To design and manufacture according to UL standard.
- Voltage according to customer's request.
- Welcome to be agents to make other products.
- Take the backplate off the bell and connect these wires to the terminal.
- Plug these connectors into terminals.

MAX
2.5mm²



Connector