



A2 GLAND FOR UNARMoured CABLE

SIZE	CABLE DIMENSIONS ACCOMODATED (mm)			GLAND DIMENSIONS (mm)				Cat. NO
	OVERALL DIAMETER A (mm)			ISO ENTRY THREAD DIA C	App. LENGTH FROM SHOULDER (D)	HEXAGON SIZE		
	Min	Max	B			A/F (G)	A/C (H)	
				mm	mm	mm	mm	
20S	8.0	11.5	20	10	22	22.0	24.9	CEA2-20S
20L	11.0	13.5	20	10	22	24.0	27.0	CEA2-20L
25S	13.0	16.5	25	10	25	30.5	34.0	CEA2-25S
25L	13.0	19.5	25	10	25	30.5	34.0	CEA2-25L
32	19.0	25.5	32	15	25	37.6	42.2	CEA2-32
40S	25.0	32.0	40	15	33	46.0	51.0	CEA2-40S
40L	25.0	32.0	40	15	33	46.0	51.0	CEA2-40L
50S	31.5	37.0	50	15	30	56.4	61.5	CEA2-50S
50L	36.5	43.0	50	15	30	56.4	61.5	CEA2-50L
63S	42.5	50.0	63	15	34	70.1	77.2	CEA2-63S
63L	49.5	55.0	63	15	32	75.0	83.0	CEA2-63L
75S	54.5	61.0	75	15	32	80.0	87.4	CEA2-75S
75L	60.5	67.0	75	15	40	85.0	95.0	CEA2-75L
90	65.0	78.0	90	20	45	106.0	117.0	CEA2-90

