



## BW GLAND FOR SWA CABLE

SIZE	CABLE DIMENSIONS ACCOMODATED			GLAND DIMENSIONS					CAT. NO
	DIAMETER		ARMOUR WIRE DIA. C MAX	ISO ENTRY THREAD		App.LENGTH FROM SHOULDER F	HEXAGON SIZE		
	ARMOUR A MAX	OVERALL B MAX		DIA D	LENGTH E		ACROSS FLATS G	ACROSS CONERS H	
mm	mm	mm	mm	mm	mm	mm	mm	mm	
16	8.6	13.2	0.9	16	10	21	20.8	23.6	CEBW-16
20S	15.8	15.8	0.9 /1.25	20	10	24	22.0	24.9	CEBW-20S
20L	21.0	21.0	0.9 /1.25	20	10	25	27.0	30.0	CEBW-20L
25S	23.8	23.8	1.25/1.60	25	10	26	31.7	35.7	CEBW-25S
25L	27.2	27.2	1.25/1.60	25	10	26	37.6	42.2	CEBW-25L
32	33.2	33.2	1.60/2.0	32	10	28	47.3	53.6	CEBW-32
40S	39.2	39.2	1.60/2.0	40	10	25	48.4	54.6	CEBW-40S
40L	39.9	39.9	1.60/2.0	40	15	25	50.0	57.0	CEBW-40L
50S	51.6	51.6	2.00/2.25	50	15	36	58.0	64.2	CEBW-50S
50L	52.2	52.2	2.00/2.25	50	15	36	65.0	71.2	CEBW-50L
63S	61.0	61.0	2.5	63	15	30	71.0	77.5	CEBW-63S
63L	65.3	65.3	2.5	63	15	30	80.0	87.4	CEBW-63L
75S	71.3	71.3	2.5	75	15	40	85.0	95.0	CEBW-75S
75L	78.0	78.0	2.5	75	15	40	98.0	109.2	CEBW-75L

