



CW GLAND FOR SWA CABLE

SIZE	CABLE DIMENSIONS ACCOMODATED			GLAND DIMENSIONS					CAT. NO
	DIAMETER		ARMOUR WIRE DIAMETER C MAX	ISO ENTRY THREAD		App.LENGTH FROM SHOULDER F	HEXAGON SIZE		
	ARMOUR A MAX	OVERALL B MAX		DIA D	LENGTH E		ACROSS FLATS G	ACROSS CONERS H	
mm	mm	mm	mm	mm	mm	mm	mm	mm	
16	8.6	13.2	0.9	16	10	40	23.4	26.7	CECW-16
20SS	8.6	13.2	0.9	20	10	40	23.4	26.7	CECW-20SS
20S	11.6	15.8	0.9 /1.25	20	10	42	25.7	29.2	CECW-20S
20L	13.9	20.8	0.9 /1.25	20	10	42	30.5	34.0	CECW-20L
25S	15.5	25.8	0.9 /1.25	25	10	48	37.6	42.2	CECW-25S
25L	19.9	27.2	0.9 /1.25	25	10	48	37.6	42.2	CECW-25L
32	26.2	33.5	1.60/2.0	32	10	51	47.3	53.6	CECW-32
40S	30.3	35.9	1.60/2.0	40	10	55	56.7	61.5	CECW-40S
40L	32.1	39.9	1.60/2.0	40	15	55	56.7	61.5	CECW-40L
50S	40.8	51.0	2.0 /2.25	50	15	60	70.1	77.2	CECW-50S
50L	44.0	52.6	2.0 /2.25	50	15	60	70.1	77.2	CECW-50L
63S	53.6	64.1	2.5	63	15	63	80.0	87.4	CECW-63S
63L	55.9	65.3	2.5	63	15	63	80.0	87.4	CECW-63L
75L	67.9	78.0	2.5	75	15	72	98.8	109.2	CECW-75L

