



# COPPER FERRULES

Material : E-Copper-BS :1977

Surface : Tin Plated

CABLE mm <sup>2</sup>	A	C	J	CAT. NO.
1.5	1.8	3.7	15	CEF 1.5 - 15
			22	CEF 1.5 - 22
2.5	2.4	4.0	15	CEF 2.5 - 15
			22	CEF 2.5 - 22
4	3.1	4.8	15	CEF 4 - 15
			25	CEF 4 - 25
6	3.8	5.5	15	CEF 6 - 15
			22	CEF 6 - 22
			25	CEF 6 - 25
10	4.5	6.2	20	CEF 10 - 20
			22	CEF 10 - 22
			30	CEF 10 - 30
16	5.4	7.1	20	CEF 16 - 20
			35	CEF 16 - 35
25	6.8	8.8	32	CEF 25 - 32
			40	CEF 25 - 40
			47	CEF 25 - 47
35	8.2	10.6	36	CEF 35 - 36
			45	CEF 35 - 45
50	9.5	12.4	40	CEF 50 - 40
			47	CEF 50 - 47
			50	CEF 50 - 50
70	11.2	14.7	40	CEF 70 - 40
			45	CEF 70 - 45
			50	CEF 70 - 50
95	13.5	17.4	45	CEF 95 - 45
			50	CEF 95 - 50
			60	CEF 95 - 60
120	15.0	19.4	45	CEF 120 - 45
			65	CEF 120 - 65
150	16.5	21.2	55	CEF 150 - 55
			65	CEF 150 - 65
185	18.5	23.5	65	CEF 185 - 65
			75	CEF 185 - 75
			80	CEF 240 - 80
240	21.0	26.5	85	CEF 240 - 85
			89	CEF 240 - 89
			85	CEF 300 - 85
300	23.5	30.0	90	CEF 300 - 90
			90	CEF 400 - 90
400	26.8	34.8	100	CEF 400 - 100
			100	CEF 500 - 100
			110	CEF 500 - 110
630	35.0	45.0	110	CEF 630 - 110
			120	CEF 630 - 120
800	39.0	50.6	150	CEF 800 - 150
1000	43.0	56.2	170	CEF1000 - 170

