


CABLE TIES

● LOCKING CABLE TIES




() Suffix "-WR" should be added if black(outdoor) color is required.

2.5 TIE BODY WIDTH	PART NO	Length	Width	Max	Tensile	Military	Installation	Package
		mm (inch)	mm (inch)	Bundle Dia,(inch)	Strength Kg(LBS)	Standard Spec,	TOOL Part No	Q ty
	DACT 80-2.3-L	80 (3.1)	2.4 (.09)	17 (.68)	8.1 (18)	MS3367-4	DAG-50	1,000
	DACT100-2.5-L	100 (4.0)		21 (0.83)				
	DACT160-2.5-L	160 (6.2)	2.5 (.10)	40 (1.57)				
	DACT200-2.5-L	205 (8.0)		52 (2.02)				
3.6 TIE BODY WIDTH	DACT140-3.6-L	146 (5.7)	3.6 (.14)	35 (1.38)	17.8 (40)	MS3367-5	DAG-50	1,000
	DACT200-3.6-L	203 (8.0)		50 (2.00)				
	DACT210-3.6-L	210 (8.26)		52 (2.04)				
	DACT300-3.6-L	300 (11.8)		77 (3.03)				
	DACT370-3.6-L	370 (14.5)		102 (4.00)				

● LOCKING CABLE TIES



() Suffix "-WR" should be added if black(outdoor) color is required.

4.8 TIE BODY WIDTH	PART NO	Length	Width	Max	Tensile	Military	Installation	Package
		mm (inch)	mm (inch)	Bundle Dia,(inch)	Strength Kg(LBS)	Standard Spec,	TOOL Part No	Q ty
	DACT120-4.8-L	120 (4.7)	4.8 (.19)	30 (1.00)	22.2 (50)	MS3367-1	DAG-50	1,000
	DACT160-4.8-L	160 (6.2)		40 (1.57)				
	DACT190-4.8-L	190 (7.5)		48 (1.89)				
	DACT200-4.8-L	200 (8.0)		52 (2.05)				
	DACT250-4.8-L	250 (10.0)		67 (2.64)		MS3367-7		500
	DACT280-4.8-L	280 (11.0)		76 (2.99)				
	DACT300-4.8-L	300 (11.8)		83 (3.27)				
	DACT370-4.8-L	368 (14.5)		102 (4.02)				

Material : 66 Nylon
 Color : Natural or Black(UV)
 Flammability: UL 94V-2 or UL94 V-0
 Service Temperature : 85

Most Dong-A Cable Ties, when tested, meet the requirements of MIL-S-23190E (or SAE AS23190)

CABLE TIES

● LOCKING CABLE TIES



() Suffix "-WR" should be added if black(outdoor) color is required.

6.3 TIE BODY WIDTH	PART NO	Length	Width	Max	Tensile	Military	Installation	Package
		mm (inch)	mm (inch)	Bundle Dia,(inch)	Strength Kg(LBS)	Standard Spec,	TOOL Part No	Q ty
	DAMCT270-6.1-L	279 (10.5)	6.1 (.24)	73 (2.87)				
	DAMCT300-6.3-L	300 (11.8)	6.3 (.24)	80 (3.15)	45.3 (100)	MS3367-3	DAG-250	100
	DAMCT370-6.3-L	370 (14.5)	6.3 (.24)	102 (4.02)				
7.6 TIE BODY WIDTH	DAMCT200-7.6-L	200 (8.0)		50 (2.00)				
	DAMCT300-7.6-L	300 (11.8)	7.6 (.30)	78 (3.07)	53.4kg (120)	MS3367-3	DAG-250	100
	DAMCT370-7.6-L	370 (14.5)		102 (4.02)				

● LOCKING CABLE TIES



() Suffix "-WR" should be added if black(outdoor) color is required.

9.0 TIE BODY WIDTH	PART NO	Length	Width	Max	Tensile	Military	Installation	Package
		mm (inch)	mm (inch)	Bundle Dia,(inch)	Strength Kg(LBS)	Standard Spec,	TOOL Part No	Q ty
	DAMCT450-9.0-L	455 (17.7)		127 (5.0)				
	DAMCT530-9.0-L	530 (20.9)		152 (6.0)				
	DAMCT650-9.0-L	650 (25.6)	9.0 (.35)	188 (7.40)	77.8 (175)	MS3367-6	DAG-250	100
	DAMCT780-9.0-L	780 (30.6)		225 (8.86)				
	DAMCT880-9.0-L	880 (34.6)		260 (10.24)				
	DAMCT1000-9.0-L	1000 (42.5)		320 (12.69)				

Material : 66 Nylon
 Color : Natural or Black(UV)
 Flammability: UL 94V-2 or UL94 V-0
 Service Temperature : 85

Most Dong-A Cable Ties, when tested, meet the requirements of MIL-S-23190E (or SAE AS23190)