

Type of Explosion-proof Flameproof (Ex d II C)



MEFM Series Flameproof Flexible Couplings

Materials

- Connector : Carbon steel or Brass or Stainless steel
- Flexible tube : Stainless steel
- Conduit Hub Type
 - M × M : Male and Male
 - M × F : Male and Female
 - F × F : Female and Female

MEFM Series



MEFM Series Flameproof Flexible Couplings

| Thread Size | Outside Diameter | Min. a Radius of bend | Flexible Length | Catalogue No. |
|--------------|------------------|-----------------------|-----------------|---------------|
| 1/2" (16C) | 40 | 80 | 500 | MEFM 1605 |
| | | | 700 | MEFM 1607 |
| | | | 1000 | MEFM 1610 |
| 3/4" (22C) | 43 | 110 | 500 | MEFM 2205 |
| | | | 700 | MEFM 2207 |
| | | | 1000 | MEFM 2210 |
| 1" (28C) | 53 | 140 | 500 | MEFM 2805 |
| | | | 700 | MEFM 2807 |
| | | | 1000 | MEFM 2810 |
| 1-1/4" (36C) | 67 | 180 | 500 | MEFM 3605 |
| | | | 700 | MEFM 3607 |
| | | | 1000 | MEFM 3610 |
| 1-1/2" (42C) | 73 | 210 | 500 | MEFM 4205 |
| | | | 700 | MEFM 4207 |
| | | | 1000 | MEFM 4210 |
| 2" (54C) | 85 | 270 | 500 | MEFM 5405 |
| | | | 700 | MEFM 5407 |
| | | | 1000 | MEFM 5410 |
| 2-1/2" (70C) | 102 | 350 | 500 | MEFM 7005 |
| | | | 700 | MEFM 7007 |
| | | | 1000 | MEFM 7010 |
| 3" (82C) | 115 | 410 | 500 | MEFM 8205 |
| | | | 700 | MEFM 8207 |
| | | | 1000 | MEFM 8210 |
| 3-1/2" (92C) | 130 | 460 | 500 | MEFM 9205 |
| | | | 700 | MEFM 9207 |
| | | | 1000 | MEFM 9210 |
| 4" (104C) | 145 | 520 | 500 | MEFM 10405 |
| | | | 700 | MEFM 10407 |
| | | | 1000 | MEFM 10410 |